



Sr. No	Rocksmith Part Number	OD (Inches)	OD (mm)	ID (Inches)	ID (mm)	Max Depth (Ft/ m)	Open Area -sq in/ ft of Screen									
							Screen Slot Size (Thousandth of an inch) / mm									
							7/0.178	10/0.25	12/0.30	20/0.50	30/0.76	40/1.00	50/1.27	60/1.52	80/2.03	100/2.54
Water Well and Environmental Screen 90 wire construction																
1	WWS-1-1	1.7	43.18	1.1	27.94	600/ 182.88	4.6	6.4	7.6	11.7	16.1	19.8	22.1	-	-	-
2	WWS-1-2	2.4	60.96	2	50.8	600/ 182.88	6.6	9.2	10.8	16.7	22.9	28.2	32.7	-	-	-
3	WWS-1-3	2.5	63.5	2	50.8	600/ 182.88	6.9	9.6	11.2	17.4	23.9	29.3	34	-	-	-
4	WWS-1-4	3	76.2	2.4	60.96	600/ 182.88	8.1	11.3	13.3	20.5	28.1	34.6	40.1	-	-	-
5	WWS-1-5	3.5	88.9	2.9	73.66	600/ 182.88	9.6	13.3	15.7	24.2	33.3	40.9	47.5	-	-	-
6	WWS-1-6	3.7	93.98	3.1	78.74	600/ 182.88	10	13.9	16.3	25.2	34.6	42.6	49.4	-	-	-
7	WWS-1-7	4.5	114.3	4	101.6	250/76.2	12.4	17.1	20.2	31.1	42.8	52.6	61	-	-	-
8	WWS-1-8	4.7	119.38	4.1	104.14	250/76.2	12.8	17.7	20.9	32.2	44.3	54.5	63.2	-	-	-
9	WWS-1-9	5.6	142.24	5	127	100/30.48	15.3	21.2	24.9	38.5	52.8	65.0	75.4	-	-	-
Free Flow 304 Stainelss Steel Screen																
1	WWS-2-1	6.5	165.1	6.0	152.4	100/30.48	-	35	-	61	82	98	111	123	140	100
2	WWS-2-2	6.6	167.64	6.0	152.4	250/76.2	-	20	-	37	51	64	75	85	102	115
3	WWS-2-3	6.7	170.18	5.9	149.86	600/ 182.88	-	20	-	37	52	65	76	86	103	117
4	WWS-2-4	6.8	172.72	5.9	149.86	1000/304.8	-	16	-	30	43	54	64	73	89	103
5	WWS-2-5	7.6	193.04	6.7	170.18	250/76.2	-	23	-	42	59	73	86	98	117	133
6	WWS-2-6	7.7	195.58	6.7	170.18	1000/304.8	-	18	-	34	48	61	73	83	101	116
7	WWS-2-7	8.7	220.98	7.9	200.66	250/76.2	-	26	-	48	67	84	99	112	134	152
8	WWS-2-8	8.8	223.52	7.9	200.66	1000/304.8	-	21	-	39	55	70	83	95	115	133
9	WWS-2-9	9.5	241.3	8.6	218.44	250/76.2	-	28	-	53	74	92	108	122	146	166
10	WWS-2-10	9.6	243.84	8.6	218.44	1000/304.8	-	23	-	43	60	76	90	103	126	145
11	WWS-2-11	10.8	274.32	9.8	248.92	600/ 182.88	-	25	-	48	68	86	102	116	142	163
12	WWS-2-12	10.8	274.32	9.8	248.92	1000/304.8	-	25	-	48	68	86	102	116	142	163



Sr. No	Rocksmith Part Number	OD (Inches)	OD (mm)	ID (Inches)	ID (mm)	Max Depth (Ft/ m)	Open Area -sq in/ ft of Screen									
							Screen Slot Size (Thousandth of an inch) / mm									
							7/0.178	10/0.25	12/0.30	20/0.50	30/0.76	40/1.00	50/1.27	60/1.52	80/2.03	100/2.54
13	WWS-2-13	11.4	289.56	10.4	264.16	600/ 182.88	-	27	-	51	72	90	107	123	149	172
14	WWS-2-14	11.4	289.56	10.4	264.16	1000/304.8	-	27	-	51	72	90	107	123	149	172
15	WWS-2-15	12.8	325.12	11.8	299.72	250/76.2	-	30	-	57	80	102	121	138	168	193
16	WWS-2-16	12.8	325.12	11.8	299.72	600/ 182.88	-	30	-	57	80	102	121	138	168	193
17	WWS-2-17	12.9	327.66	11.8	299.72	1000/304.8	-	29	-	55	78	98	117	134	163	188
18	WWS-2-18	12.6	320.04	11.6	294.64	250/76.2	-	30	-	56	79	100	119	136	165	190
19	WWS-2-19	12.6	320.04	11.6	294.64	600/ 182.88	-	30	-	56	79	100	119	136	165	190
20	WWS-2-20	12.6	320.04	11.6	294.64	1000/304.8	-	28	-	53	76	96	114	136	160	184
21	WWS-2-21	14.1	358.14	13.1	332.74	250/76.2	-	33	-	63	89	112	133	152	185	213
22	WWS-2-22	14.1	358.14	13.1	332.74	600/ 182.88	-	33	-	63	89	112	133	152	185	213
23	WWS-2-23	14.1	358.14	13.1	332.74	1000/304.8	-	32	-	60	85	107	128	146	179	206
24	WWS-2-24	16.1	408.94	15	381	100/30.48	-	38	-	71	101	128	152	173	211	243
25	WWS-2-25	16.1	408.94	15	381	250/76.2	-	38	-	71	101	128	152	173	211	243
26	WWS-2-26	16.1	408.94	15	381	600/ 182.88	-	36	-	68	97	123	146	167	204	235
27	WWS-2-28	16.1	408.94	14.8	375.92	1000/304.8	-	40	-	75	106	133	158	180	219	251
28	WWS-2-29	17.9	454.66	16.7	424.18	100/30.48	-	42	-	79	112	142	169	193	235	270
29	WWS-2-30	17.9	454.66	16.7	424.18	250/76.2	-	40	-	76	108	136	162	186	227	262
30	WWS-2-31	18.0	457.2	16.7	424.18	600/ 182.88	-	45	-	84	118	149	177	202	245	280
31	WWS-2-32	18.0	457.2	16.7	424.18	1000/304.8	-	45	-	84	118	149	177	202	245	280
32	WWS-2-33	19.9	505.46	18.8	477.52	100/30.48	-	47	-	88	125	158	188	214	261	300
33	WWS-2-34	20.1	510.54	18.8	477.52	250/76.2	-	45	-	85	120	152	181	208	253	292
34	WWS-2-35	20.1	510.54	18.8	477.52	600/ 182.88	-	50	-	94	132	167	197	225	273	313



Sr. No	Rocksmith Part Number	OD (Inches)	OD (mm)	ID (Inches)	ID (mm)	Max Depth (Ft/ m)	Open Area -sq in/ ft of Screen									
							Screen Slot Size (Thousandth of an inch) / mm									
							7/0.178	10/0.25	12/0.30	20/0.50	30/0.76	40/1.00	50/1.27	60/1.52	80/2.03	100/2.54
35	WWS-2-36	20.1	510.54	18.8	477.52	1000/304.8	-	50	-	94	132	167	197	225	273	313
36	WWS-2-37	21.9	556.26	20.7	525.78	100/30.48	-	52	-	97	138	174	206	236	287	330
37	WWS-2-38	21.9	556.26	20.7	525.78	250/76.2	-	49	-	93	132	167	198	227	278	320
38	WWS-2-39	22	558.8	20.7	525.78	600/ 182.88	-	55	-	102	145	182	216	246	299	343
39	WWS-2-40	22.2	563.88	20.7	525.78	1000/304.8	-	42	-	80	114	146	174	201	248	289
40	WWS-2-41	24.1	612.14	22.8	579.12	100/30.48	-	54	-	102	145	184	218	250	305	352
41	WWS-2-42	24.2	614.68	22.8	579.12	250/76.2	-	60	-	113	159	201	238	271	329	377
42	WWS-2-43	24.4	619.76	22.8	579.12	1000/304.8	-	46	-	88	125	160	192	221	273	317
Large Diameter Hi-Flow SS304 Stainless Steel Screen																
1	WWS-3-1	6.5	165.1	6.0	152.4	100/30.48	-	35	-	61	82	98	111	123	140	153
2	WWS-3-2	6.6	167.64	6.0	152.4	250/76.2	-	25	-	46	63	77	90	100	118	132
3	WWS-3-3	6.7	170.18	5.9	149.86	600/ 182.88	-	26	-	46	64	78	91	102	120	134
4	WWS-3-4	6.7	170.18	5.9	149.86	1000/304.8	-	26	-	46	64	78	91	102	120	134
5	WWS-3-5	7.5	190.5	6.7	170.18	100/30.48	-	40	-	71	94	113	129	141	162	177
6	WWS-3-6	7.5	190.5	6.7	170.18	600/ 182.88	-	29	-	52	71	88	102	114	134	150
7	WWS-3-7	7.6	193.04	6.7	170.18	1000/304.8	-	35	-	63	85	103	118	131	152	168
8	WWS-3-8	8.7	220.98	7.9	200.66	250/76.2	-	36	-	66	90	111	129	144	170	189
9	WWS-3-9	8.7	220.98	7.9	200.66	1000/304.8	-	44	-	79	106	129	148	164	190	209
10	WWS-3-10	10.8	274.32	9.8	248.92	250/76.2	-	50	-	89	121	147	168	186	216	238
11	WWS-3-11	10.9	276.86	9.8	248.92	1000/304.8	-	29	-	55	77	97	114	130	157	179
12	WWS-3-12	11.3	287.02	10.4	264.16	250/76.2	-	53	-	94	127	154	176	195	226	249
13	WWS-3-13	11.4	289.56	10.4	264.16	1000/304.8	-	31	-	57	81	101	119	136	164	187



Sr. No	Rocksmith Part Number	OD (Inches)	OD (mm)	ID (Inches)	ID (mm)	Max Depth (Ft/ m)	Open Area -sq in/ ft of Screen									
							Screen Slot Size (Thousandth of an inch) / mm									
							7/0.178	10/0.25	12/0.30	20/0.50	30/0.76	40/1.00	50/1.27	60/1.52	80/2.03	100/2.54
14	WWS-3-14	12.8	325.12	11.8	299.72	250/76.2	-	60	-	106	143	174	199	221	256	282
15	WWS-3-15	12.9	327.66	11.8	299.72	1000/304.8	-	35	-	65	91	114	135	154	185	211
16	WWS-3-16	12.5	317.5	11.6	294.64	250/76.2	-	58	-	104	140	170	195	216	250	276
17	WWS-3-17	12.6	320.04	11.6	294.64	1000/304.8	-	34	-	63	89	112	132	150	181	207
18	WWS-3-18	14	355.6	13.1	332.74	250/76.2	-	65	-	116	157	190	218	242	280	309
19	WWS-3-19	14.1	358.14	13.1	332.74	1000/304.8	-	38	-	71	100	125	148	168	202	231
20	WWS-3-20	16.1	408.94	15	381	100/30.48	-	75	-	133	180	219	251	278	322	355
21	WWS-3-21	16.1	408.94	15	381	600/ 182.88	-	43	-	81	111	143	169	192	231	264
22	WWS-3-22	16.3	414.02	15	381	1000/304.8	-	40	-	76	107	135	160	183	221	254
23	WWS-3-23	17.9	454.66	16.7	424.18	600/ 182.88	-	48	-	90	127	159	187	213	257	293
24	WWS-3-24	18	457.2	16.7	424.18	1000/304.8	-	45	-	84	118	149	177	202	245	280
25	WWS-3-25	20	508	18.8	477.52	250/76.2	-	54	-	101	141	177	209	238	287	328
26	WWS-3-26	20.1	510.54	18.8	477.52	600/ 182.88	-	50	-	94	132	167	197	225	273	313
27	WWS-3-27	20.1	510.54	18.8	477.52	1000/304.8	-	54	-	101	142	178	210	239	289	329
28	WWS-3-28	21.9	556.26	20.7	525.78	250/76.2	-	59	-	110	155	194	229	261	315	359
29	WWS-3-29	22.0	558.8	20.7	525.78	600/ 182.88	-	55	-	102	145	182	216	246	299	343
30	WWS-3-30	22.2	563.88	20.7	525.78	1000/304.8	-	42	-	80	114	146	174	201	248	289
31	WWS-3-31	24.1	612.14	22.8	579.12	100/30.48	-	65	-	121	170	214	252	287	346	395
32	WWS-3-32	24.2	614.68	22.8	579.12	250/76.2	-	60	-	113	159	201	238	271	329	377
33	WWS-3-33	24.4	619.76	22.8	579.12	1000/304.8	-	46	-	88	125	160	192	221	273	317